


To whom it may concern;

## Product Specification

1. Product Name: #248G Heat-resistant harness tape

2. Adhesive Tape Structure



3. Specifications

Nominal Dimension		
Thickness (mm)	Width (mm)	Length (m)
0.15	19	20

4. Standard Color

Black	Gray	-	-
-------	------	---	---

5. Performance Data

Property		Specification	Testing Method
Thickness	(mm)	0.15 ± 0.03	JIS Z 0237
Width	(mm)	19 ± 1.0	JIS Z 0237
Length	(m)	20 or larger	JIS Z 0237
Peeling		No transfer of adhesive to next backing	JIS Z 0237
Tensile strength N/19mm{kgf/19mm}	At room temperature	29.4{3.0} or larger	JIS Z 0237
	After heating	29.4{3.0} or larger	—
Elongation %	At room temperature	125 or larger	JIS Z 0237
	After heating	100 or larger	—
Adhesive strength to backing N/10 mm{gf/10mm}		0.69{70.0} or larger	JIS Z 0237
Lap joint adhesive strength N/19mm{kgf/19mm}	At room temperature	29.4{3.0} or larger	—
	After heating	29.4{3.0} or larger	—
Volume resistivity	MΩ·cm	1.0 × 10 <sup>6</sup> or larger	JIS C 2107-Appendix JA.2
Withstand voltage		Withstanding at 5000V x 1 minute	JIS C 2107-Appendix JA.1
Cold resistance		No crack at -10°C	—
Heat resistance* <sup>1</sup>		No melt of <u>main base material</u> after heating at 200°C x 30 minutes	—
Flame retardance		Extinguishing in 30 seconds	UL 510

\*<sup>1</sup> Adhesive is not covered by quality assurance.

6. Instructions for Use and Storage (Precautions)

- When you handle or store product, mind to avoid from direct sunlight or storage in high temperature place.
- Please use product after cleaning and removing stain, dust, moisture or oils on the surface of product.
- When you use product, mind to test the suitability of product for particular purpose or its safety beforehand by yourself and make sure on your own responsibility.